

XLE OCS

Massive Features Engineered within a Compact Package

Complete control, I/O, networking & HMI capabilities empowered by a streamlined design



APPLICATIONS

Agriculture

- Reduce energy consumption
- Increase overall productivity

Building Automation

- Improve occupant comfort
- Economical operation systems

Material Handling

- Minimise HMI inefficiencies
- Track/log/catalogue data

Oil and Gas

- Maximise capacity utilisation
- Maintain emission standards

Renewable Energy

- Data logging, remote access
- Sunlight and UV protection

Water/Wastewater

- Station pump control
- Remote water well controls

Manufacturing

- Production management and control
- Datalogging

COMPACT PHYSICAL DESIGN

The small, dense design of the XLE enables you to fit more in your panel, saving space and resources. For an introductory XL Series product, the XLE packs big solutions into an overall small package, utilising a standard quarter DIN (92x92mm) cutout.

FLEXIBLE I/O CONFIGURATION

The XLE is engineered with six unique built-in I/O configurations (five optional models and one without I/O), all of which include high speed counting capabilities - a truly advantageous feature for such a small package! If the built-in I/O of the XLE isn't enough for your specific application, you can easily expand via CAN or Ethernet serial. With billions of external I/O combinations through several additional networking media, the wide scope of digital and analogue I/O make automating your applications, and your organisation, as simple as the push of a button.

EXTENSIVE CONTROL & HMI FEATURES

Many of the features found in more high-end controllers are available in our XLE OCS controller. The XLE utilises a sunlight readable backlit screen (good for dark and sunlight), physical keys for buttons, and a strong graphical user interface which deeply integrates the HMI into the control system. Some of the strengths and benefits of the XLE are:

- **Datalogging:** massive data storage for later analysis or recall
- **Scheduling:** easily enable period and time-based measurements/events; includes standard real time clock
- **Floating point and advanced maths:** comprehensive functions easily performs complex mathematical processing
- **Multi language support:** easily integrate into diverse markets through one product: custom fonts for different languages, symbols, or sizes.

COMPREHENSIVE CONNECTIVITY

The level and scope of connectivity within the XLE is unprecedented. Compatible with Ethernet (optional), CAN, USB, RS232, RS485, the XLE makes communicating to other systems seamless and easy. The XLE employs an array of physical connections, as well as a host of protocols enabling communication in a multitude of languages: allowing the unit to communicate with various equipment within different industrial manufactured components.

SPECIFICATIONS AND TECHNICAL INFORMATION



PHYSICAL CHARACTERISTICS

- 1 DIN rail mounting clip
- 2 Wide-range DC power
- 3 CAN port
- 4 Ethernet LAN Port (optional)
- 5 High capacity microSD slot
- 6 RS232/RS485 serial ports
- 7 USB mini-B port
- 8 Transflective LCD screen
- 9 Programmable soft keys
- 10 Numeric / Function keys

CONTROLLER	
CPU	High Performance 32 Bit Arm with DSP and FPU Acceleration
Logic Scan Rate	0.7 mS/K
Built-In Storage	16Mb
Removable Memory	32GB microSD
Retentive Storage	32K Battery-Backed Ram
Programming Languages	Advanced Ladder or IEC: ST, LD, FBD, IL, SFC
USER INTERFACE	
Display Technology	2.2" Transflective LCD
Resolution / Color	128 x 64, Monochrome
Keypad	20 Key Domed Membrane
CONNECTIVITY	
Serial Ports	2 Ports with RS-232 and RS-485
USB Ports (Mini-B)	1 Programming
Ethernet	10/100 Support with Auto MDIX Support (optional)
CAN	1 Port 125Kb - 1Mb

STANDARD	ETHERNET	I/O MODELS
HEXE220C100	HEXE221C100	No Built-in I/O
HEXE220C112	HEXE221C112	12 DC In, 6 Relay Out, 4 - 12-bit Analogue In
HEXE220C113	HEXE221C113	12 DC in, 12 DC Out, 2 - 12-bit Analogue In
HEXE220C114	HEXE221C114	24 DC in, 16 DC Out, 2 - 12-bit Analogue In
HEXE220C115	HEXE221C115	12 DC in, 12 DC Out, 2 - 14/16-bit Analogue In (mA/V/Tc/mV/RTD), 2 - 12-bit Analogue Out
HEXE220C116	HEXE221C116	12 DC in, 12 DC Out, 6 - 14/17-bit Analogue In (mA/V/Tc/mV/RTD), 4 - 12-bit Analogue Out
Remote I/O		All Models Support SmartRail, SmartBlock, SmartStix, SmartMod, various 3rd party I/O devices

OPERATING SPECS. & STANDARDS	
Primary Power Range	10-30VDC
Power	1-5W (depending on model/configuration)
Operating Temperature	-10° to 60° C
Humidity (non-condensing)	5 to 95% Non-Condensing
Environmental Ratings	IP65, UL Type 3R, 4, 4x, 12, 12k, 13

PHYSICAL SPECIFICATIONS	
Dimensions	mm: 96.0 tall x 96.0 wide x 57.5 deep in: 3.78 tall x 3.78 wide x 2.26 deep