

# XLT OCS

## Massive Features Engineered within a Compact Package

Complete control, I/O, networking & HMI capabilities empowered by a streamlined design



### APPLICATIONS

#### Agriculture

- Reduce energy consumption
- Increase overall productivity

#### Building Automation

- Improve occupant comfort
- Economical operation systems

#### Material Handling

- Minimise HMI inefficiencies
- Track/log/catalog data

#### Oil and Gas

- Maximise capacity utilisation
- Maintain emission standards

#### Renewable Energy

- Data logging, remote access
- Sunlight and UV protection

#### Water/Wastewater

- Station pump control
- Remote water well controls

#### Manufacturing

- Production management and control
- Datalogging

### COMPACT PHYSICAL DESIGN

The small, dense design of the XLT enables you to fit more in your panel, saving space and resources. For an introductory XL Series product, the XLT packs a big picture into an overall small package, utilizing a standard quarter DIN (92x92mm) cutout.

### FLEXIBLE I/O CONFIGURATION

The XLT is engineered with six unique built-in I/O configurations (five optional models and one without I/O), all of which include high speed counting capabilities - a truly advantageous feature for such a small package! If the built-in I/O of the XLT isn't enough for your specific application, you can easily expand via CAN or Ethernet serial. With billions of external I/O combinations through several additional networking media, the wide scope of digital and analogue I/O make automating your applications, and your organisation, as simple as the push of a button.

### EXTENSIVE CONTROL & HMI FEATURES

Many of the features found in more high-end controllers are available in our XLT OCS controller. The XLT utilizes a sunlight readable backlit touchscreen (good for dark and sunlight), physical keys for buttons, and a strong graphical user interface which deeply integrates the HMI into the control system. Some of the strengths and benefits of the XLT are:

- **Datalogging:** massive data storage for later analysis or recall
- **Scheduling:** easily enable period and time-based measurements/events; includes standard real time clock
- **Floating point and advanced maths:** comprehensive functions easily performs complex mathematical processing
- **Multi language support:** easily integrate into diverse markets through one product: custom fonts for different languages, symbols, or sizes.

### COMPREHENSIVE CONNECTIVITY

The level and scope of connectivity within the XLT is unprecedented. Compatible with Ethernet (optional), CAN, USB, RS232, RS485, the XLT makes communicating to other systems seamless and easy. The XLT employs an array of physical connections, as well as a host of protocols enabling communication in a multitude of languages: allowing the unit to communicate with various equipment within different industrial manufactured components.

## SPECIFICATIONS AND TECHNICAL INFORMATION



### PHYSICAL CHARACTERISTICS

- 1 DIN rail mounting clip
- 2 Wide-range DC power
- 3 CAN port
- 4 Ethernet LAN Port (optional)
- 5 High capacity microSD slot
- 6 RS232/RS485 serial ports
- 7 USB mini-B port
- 8 Transflective LCD touchscreen
- 9 Function keys

### CONTROLLER

CPU	High Performance 32 Bit Arm with DSP and FPU Acceleration
Logic Scan Rate	0.7 mS/K
Built-In Storage	16Mb
Removable Memory	32GB microSD
Retentive Storage	32K Battery-Backed Ram
Programming Languages	Advanced Ladder or IEC: ST, LD, FBD, IL, SFC

### USER INTERFACE

Display Technology	3.5" Transflective LCD
Resolution / Color	160 x 128, Monochrome
Keypad	5 Key Domed Membrane

### CONNECTIVITY

Serial Ports	2 Ports with RS-232 and RS-485
USB Ports (Mini-B)	1 Programming
Ethernet	10/100 Support with Auto MDIX Support (optional)
CAN	1 Port 125Kb - 1Mb

STANDARD	ETHERNET	I/O MODELS
HEXT240C100	HEXT241C100	No Built-in I/O
HEXT240C112	HEXT241C112	12 DC in, 6 Relay Out, 4 - 12-bit Analogue In
HEXT240C113	HEXT241C113	12 DC in, 12 DC Out, 2 - 12-bit Analogue In
HEXT240C114	HEXT241C114	24 DC in, 16 DC Out, 2 - 12-bit Analogue In
HEXT240C115	HEXT241C115	12 DC in, 12 DC Out, 2 - 14/16-bit Analogue In (mA/V/Tc/mV/RTD), 2 - 12-bit Analogue Out
HEXT240C116	HEXT241C116	12 DC in, 12 DC Out, 6 - 14/17-bit Analogue In (mA/V/Tc/mV/RTD), 4 - 12-bit Analogue Out
Remote I/O		All Models Support SmartRail, SmartBlock, SmartStix, SmartMod, various 3rd party I/O devices

### OPERATING SPECS. & STANDARDS

Primary Power Range	10-30VDC
Power	1-5W (depending on model/configuration)
Operating Temperature	-10° to 60° C
Humidity (non-condensing)	5 to 95% Non-Condensing
Environmental Ratings	IP65, UL Type 3R, 4, 4x, 12, 12k, 13

### PHYSICAL SPECIFICATIONS

Dimensions	mm: 96.0 tall x 96.0 wide x 57.5 deep in: 3.78 tall x 3.78 wide x 2.26 deep
------------	--